



Ming Feng Lighting Co.,Ltd

Address: Building 2, Zao San Street 5th,Dongcheng District,
Dongguan City,Guangdong province,P.R.China.
Tel: +86-769-2332-0862 **Fax:**+86-769-2203-6052
Email: Sales@mingfeng-lighting.com



MF LED Tri-proof Lights Data Sheet

Item No.

MF-LL015032,45,80W;MF-LL012024,24,35,50W;
MF-LL060012,18,20,24W;

Lighting Data

Electrical Data

LED Type	Lumileds	Power Supply	CE/SAA certified driver
System Efficacy	130lm/W,150lm/W	Input Voltage	100~240V ac, DC 12 -24V
System Power Consumption	12W ~ 80W	Power Frequency	50~60Hz
CCT	2700K,3000K, 4000K, 5000K	EMC/LVD	SGS certified
Beam Angle	120°	Class Rate	Class II
CRI	Ra70/Ra80/Ra90+	Power Efficiency	>90%
UGR	<19	Power Factor	>0.90
SDCM	<5	Total Harmonic Distortion	<20%

Material Data

Packing Data

Fixture Material	Alu.+PC	Junction Temperature(Tj)	<70°C(Ta=30°C)
Tube	Mist/Transparent as options	Storage Temperature	-40~+70°C
Cable	3x0.75mm	Operating Temperature	-30~+50°C
Ingress Protection	IP66/IP69K	Outlook Size(MM)	Refer to specified drawings
Life Span	10 years at 12 hours/day	Export Carton Size	Refer to specified data sheet

Optional Info.

Installation Method	Wall mount	Certificates
Fixture Color	White	
Intelligent Control	1~10V Dim/DALi control/PWM	

Job Reference

Light Distribution Curve

