



Ming Feng Lighting Co.,Ltd

Address: Building 2, Zao San Street 5th,Dongcheng District,
Dongguan City,Guangdong province,P.R.China.
Tel: +86-769-2332-0862 **Fax:**+86-769-2203-6052
Email: Sales@mingfeng-lighting.com



MF31A LED Wall Pack Light Data Sheet

Item No.

MF31A-30,50,75

Lighting Data

Electrical Data

LED Type	Lumileds	Power Supply	CE Driver/Meanwell
System Efficacy	130lm/W±5%(CCT=4000K)	Input Voltage	100~240V ac,347-480V ac
System Power Consumption	30W ~ 75W	Power Frequency	50~60Hz
CCT	2700K,3000K, 4000K, 5000K	Output Voltage	28.8~48VDC
Beam Angle	Symetric and Asymetric	Output Current	2.0A(Constant Current)
CRI	Ra70/Ra80/Ra90+	Power Efficiency	>90%
System Efficiency	>90%	Power Factor	>0.90
SDCM	<5	Total Harmonic Distortion	<20%

Material Data

Packing Data

Fixture Material	Alu.alloy+PC	Junction Temperature (Tj)	<70°C(Ta=30°C)
Paintings	AkzoNobel	Storage Temperature	-40~+60°C
Cable	3x0.75mm	Operating Temperature	-40~+40°C
Ingress Protection	IP65	Outlook Size(In)	8.27*3.65*6.69/10.43*4.25*9.64
Plug socket	Connector	Cutting Size(MM)	N/A
Life Span	7 years at 12 hours/day	Export Carton Size	Refer to specified data sheet

Senior Info.

Installation Method	Wall mount with bracket
Fixture Color	Grey/Black/White
Intelligent Control	Sensor
Adjustable Angle	Yes

Certificates

Job Reference

Light Distribution Curve

